

UMBRELLA BASE GUIDE **BY APPLICATION**

● **TABLE USE:** Indicates the base is suitable for use beneath a table. It is not recommended as a free-standing base option.

● **FREE-STANDING:** Indicates the base is recommended as a free-standing option, but also suitable for use beneath a table if the table provides enough clearance to safely sit above the base on a flat surface. 18" (18ST/2) Stems should always be used when in this application.

● **1.5"/38mm STEM:** Indicates the base can accommodate an 1.5"/38mm center pole.

● **2"/50mm STEM:** Indicates the base can accommodate a 2"/50mm (18ST2) center pole.

	7.5' OCT. / 2.3m	9' OCT. / 2.7m	11' OCT. / 3.5m	13' OCT. / 4m	6.5' SQ. / 2m	7.5' SQ. / 2.3m	10' SQ. / 3m	8' X 10' REC. / 3m	8.5' X 11' REC. / 3.5m
ALUMINUM SHELL									
502A	● ●				● ●				
RESIN COATED									
50C	● ●	● ●	● ●		● ●	● ●		● ●	
23	● ●	● ●	● ●		● ●	● ●		● ●	
ALUMINUM CONCRETE									
100A	● ● ●	● ● ●	● ● ●		● ● ●	● ●		● ●	
150A	● ● ●	● ● ●	● ● ●	● ●	● ● ●	● ● ●	● ●	● ● ●	● ●
STEEL PLATE									
50S	● ●	● ●	● ●		● ●	● ●		● ●	
75S	● ●	● ●	● ●		● ●	● ●			
GALVANIZED STEEL									
24G	● ● ●	● ● ●	● ●		● ● ●	● ●		● ●	
30G	● ● ●	● ● ●	● ● ●		● ● ●	● ● ●		● ● ●	
36G	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
40G	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
20G-SQ	● ● ●	● ●	● ●		● ●	● ●		● ●	
24G-SQ	● ● ●	● ● ●	● ● ●		● ● ●	● ● ●		● ●	
36G-SQ	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●
WHEEL BASE									
ARU/ECU-480	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●	● ●

NOTE: 18" stems (18ST/2) are recommended for free-standing applications. Frankford will not recommend a free-standing application with a shorter stem. The 75S (16" stem) is considered a free-standing base as noted above.